



# Padded jacket in 'clean' look for business and leisure

Smooth outside, inside in stitching, with DuPont<sup>™</sup> Sorona® padding (renewable, organic raw material) Wind- and waterproof fabric (5,000 mm water column) Breathable and permeable to water vapour (1,500 g/m²/24h) Stand-up collar Adjustable, detachable hood Full-length concealed front zip 2 front pockets, 2 sewn-on breast pockets, 1 zipped inner pocket Elastic inner sleeve bands Zip for decoration at the back YKK-zips JN1157 : Elastic inner cord for waist adjustmen

Fabric:

Outer fabric: 100% polyester Lining: 100% polyamide Padding: 100% polyester

Country of origin:

Myanmar (Burma)

**Care instructions** 



#### Partner article



Ladies' Business Jacket Art-Nr.: JN1157

Available colours

	S	м	L	XL	XXL	3XL
Weight in g	726g	742g	776g	812g	839g	876g
VPE (pcs. per inner packaging / pcs. per outer packaging)	1/25	1/25	1/25	1/25	1/25	1/25
measurements in	S	м	L	XL	XXL	3XL
cm						
1/2 chest:	55,00 cm	58,00 cm	61,00 cm	64,00 cm	67,00 cm	70,00 cm
length from	72,00 cm	74,00 cm	76,00 cm	78,00 cm	79,50 cm	81,00 cm
shoulder:						
sleeve length:	68,00 cm	69,00 cm	70,00 cm	71,00 cm	72,00 cm	73,00 cm

Available colours



black-melange (447C)

graphite (432C)

### Features



### DuPont<sup>™</sup> Sorona®

Sorona® renewably sourced fiber delivers superior performance benefits to today's fashions. Fabrics that use Sorona® are very soft, very strong and dry quickly. Sorona® helps fabrics stretch comfortably and retain their shape. And, it is made with plant-based ingredients. DuPont<sup>™</sup> Sorona®. Designed for Performance. Derived from Nature.





Functional textiles must have the ability to transport moisture from the skin to the fabric surface as fast as possible. Permeability shows how much steam in grams can evaporate on a surface of 1 m2 within 24 hours. The higher this figure, the more breathable the textile is.



## Water column from 1.500 mm

The ability to withstand water pressure without moisture penetrating into the material is given by the water column (mm). The minimum standard is a water column of 1,500 mm.

